

CODE NUMBER

34000007

DESCRIPTION

4-4.5/2-2.5 Lpf, Filtered, Yellow Brass Finish, Fixture Connection Rear Spud, Dual Flush, TruFlush Concealed Manual Water Closet Flushometer.

DETAILS

- Flush Volume: 4-4.5/2-2.5 Lpf (1.1-1.2/0.5-0.7 gpf)
- Finish: Yellow Brass
- Bypass: Filtered
- Fixture Type: Water Closet
- Fixture Connection: Rear Spud

FEATURES

- True flushometer provides accurate flush volume
- Heavy-duty rough brass valve body
- Vandal-resistant wall plate with easy to push button
- Replaceable piston assembly accessible through front wall plate
- Concealed shut off sleeve adjusts flow rate

**RECOMMENDED SPECIFICATION**

Valve shall be concealed with front access wall plate smaller than 7" x 7" and shall have integrated control stop.

VALVE OPERATING PRESSURE (FLOWING)

20-80 PSI (138-552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- [TRF-1036-N, 1024-N Manual Dual Flush India Installation Instructions - India](#)
- [TRF-1000 Manual Dual Flush Wall Plate Installation Instructions - India](#)
- [TRF-1036-N, 1024-N Manual Dual Flush Valve Repair and Maintenance Guide - India](#)

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the TRF-1024-N product? [View the general spec sheet with all options.](#)